




Features

- Desktop AC to DC Adapter
- Two Pins Socket – IEC320-C8
- Maximum output power: 24W
- Wide range input voltage: 90 - 265 Vac
- Output Range: See Table below
- Output DC pin type: *upon request*
- Short circuit and overload protection
- Applicable standard: See Above

Input Specifications		
Parameters	Unit	Value
Input Voltage	90 - 265	Vac
Input Frequency	50 – 60	Hz
Output Specifications		
Parameters	Value	Unit
Output Voltage Adjustable Range	9 to 24	V
Load Regulation	± 5	%
Maximum Output Ripple Voltage Peak to Peak	120	mV
Electronic Protection (shutdown and restart)	1.2 x I _{max}	Adc
Hold-up Time - Minimum	8	ms
Minimum Efficiency	83	%
General Specifications		
Parameters	Value	Unit
Dynamic Operating Range of Temperature	-10 to 50	°C
Storage Temperature	-20 to 85	°C
Relative Humidity (non-condensing)	5 to 95	%
Primary to Secondary Isolation for 1mn	3000	Vac
Primary to Secondary Insulation Resistor @500V	100	MΩ

Enclosure Outline



Models			
Ordering Code	Output Power (max.)	Output Voltage (nom.)	Output Current (max.)
MC24 – 09.0V2.60A-D	24W	9.0V	2.60A
MC24 – 12.0V2.00A-D	24W	12.0V	2.00A
MC24 – 15.0V1.60A-D	24W	15.0V	1.60A
MC24– 18.0V1.30A-D	24W	18.0V	1.30A
MC24 – 24.0V1.00A-D	24W	24.0V	1.00A

MCK HONGKONG LIMITED

Sales & R&D Office: Room 915, Dongming Building, Minkang Road, Minzhi,
Baoan Shenzhen 518129, China

Tel: +86 755-2946-9399

Mobile: +86 130-0888-5129

Email: sales@hk-mck.com

Website: www.mck-power.com